



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 1/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **MKR-0124**  
Product name: **Propylene glycol monomethyl ether acetate(PMA\parPM \parpar ACETATE)**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **not available**

#### 1.3. Details of the supplier of the safety data sheet

Name: **Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih. San. Tic. Ltd. Şti.**  
Full address: **ULUDAĞ ORGANİZE SANAYİ BÖLGESİ KALE MAH.KILIÇLAR CAD. NO:10 KESTEL**  
District and Country: **16450 BURSA**  
**TR**  
Tel. **+90 224 372 50 23**  
Fax **+90 224 372 50 29**

#### 1.4. Emergency telephone number

For urgent inquiries refer to: **+90 224 372 50 23**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3

H226

Flammable liquid and vapour.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



MİKRO TEKNİK  
Chemical solutions

Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 2/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH



Signal words: Warning

Hazard statements:

**H226** Flammable liquid and vapour.

Precautionary  
statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**P280** Wear protective gloves/ protective clothing / eye protection / face protection.

**P370+P378** In case of fire: use . . . to extinguish.

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration 0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		
INDEX 607-195-00-7	50	Flam. Liq. 3 H226
	x < 100	
EC 203-603-9		
CAS 108-65-6		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary:  
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.  
INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person.  
EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 3/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.



MİKRO TEKNİK  
Chemical solutions

Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 4/14

Replaced revision:1 (Printed on: 12/12/2024)

MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733 EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
GBR	United Kingdom	
EU	OEL EU	

### 2-METHOXY-1-METHYLETHYL ACETATE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 5/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

#### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	Colorless clear	
Odour	not available	
Melting point / freezing point	-67 °C	
Initial boiling point	146 °C	



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 6/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

Flammability	Flammable	
Lower explosive limit	15	
Upper explosive limit	7	
Flash point	42 °C	
Auto-ignition temperature	3545 °C	
Decomposition temperature	not available	
pH	4	Concentration: 200g/L % Temperature: 20 °C
Kinematic viscosity	not available	
Solubility	Miscible with water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0.96	
Relative vapour density	4.6	
Particle characteristics	not applicable	

### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 7/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### 10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

#### Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 8/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

**Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

**2-METHOXY-1-METHYLETHYL ACETATE**

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

**2-METHOXY-1-METHYLETHYL ACETATE**

LD50 (Dermal):

> 5000 mg/kg Rat

LD50 (Oral):

8530 mg/kg Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class





**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 9/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

**Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Information not available



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 10/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### 12.2. Persistence and degradability

2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

### 12.3. Bioaccumulative potential

2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water 1,2

### 12.4. Mobility in soil

Information not available

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3272



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 11/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### 14.2. UN proper shipping name

ADR / RID: ESTERS, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

IMDG: ESTERS, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

IATA: ESTERS, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



### 14.4. Packing group

ADR / RID, IMDG, IATA: III

### 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30

Limited  
Quantities: 5  
L

Tunnel  
restriction  
code: (D/E)

Special provision: -

IMDG: EMS: F-E, S-D

Limited  
Quantities: 5  
L

IATA: Cargo:

Maximum  
quantity: 220  
L

Packaging  
instructions:  
366

Passengers:

Maximum  
quantity: 60 L

Packaging  
instructions:  
355

Special provision:

A3

### 14.7. Maritime transport in bulk according to IMO instruments



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 12/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

**Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 13/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

**Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**Flam. Liq. 3** Flammable liquid, category 3  
**H226** Flammable liquid and vapour.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148



**MİKRO TEKNİK**  
Chemical solutions

**Mikro Teknik Kimyevi Mad. Lab. Malz. ve Cih.  
San. Tic. Ltd. Şti.**

Revision nr. 2

Dated 12/12/2024

Printed on 12/12/2024

Page n. 14/14

Replaced revision:1 (Printed on: 12/12/2024)

**MKR-0124 - Propylene glycol monomethyl  
ether acetate(PMA\parPM \parpar ACETATE)**

**Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Begüm ALTUNKAYA

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

02 / 05 / 06 / 08 / 09 / 13 / 14 / 15.